

Cobra LifeLink Multi-Man System was tested by dropping 960 lbs. 6 feet simulating (3) 310 men falling simultaneously.

Cobra LifeLink Twin-Man System was tested by dropping 350 lbs. 6 feet simulating (1) 310 man falling.

INDEPENDENTLY VERIFIED TESTING RESULTS

Both Cobra LifeLink Fall Protection Systems have been tested by a nationally recognized independent laboratory and found to be in compliance with OSHA regulation 1926.502(d) for Personal Fall Arrest Systems. Printed copies available on request.



SPECIFICATIONS

Both Cobra LifeLink Twin and Multi-Man systems feature a wide range of motion for worker productivity. The carts are positioned 15' from the leading edge giving workers 20' of leading edge access before repositioning cart.

OPTIONAL EQUIPMENT for COBRA MULTI-MAN CART



Additional Toolbox




Material Rack



Carry Generators or Compressors

Rear Wheel Lock

OPTIONAL EQUIPMENT for COBRA TWIN-MAN CART



• 57 or 90 lb. Steel Weights

• 57 or 90 lb. Cement Wt Cans

COBRA MULTI-MAN

Length..(with handle).....	102"
Width.....	59"
Height.....	48"
Weight.....	1000 lbs.
Fall Arrest Rating.....	3 persons
Fall Restraint Rating.....	2 persons
Tires.....	18 x 8.50 Flat-free
Deck Space.....	25" x 40"
ToolBox.....	16 cu. ft.

COBRA TWIN-MAN

Length..(less handle).....	50"
Width.....	30"
Height.....	16"
Weight.....	600 lbs.
Fall Arrest Rating.....	1 person
Fall Restraint Rating.....	1 person
Tires.....	4.10 x 3.50 Flat Free
Counterweights.....	(6) 90 lbs. or (10) 57 lbs.



COBRA LIFELINK

PATENT PENDING

MOBILE FALL PROTECTION SYSTEMS

When Everything Is On the Line



Cobra LifeLink Multi-Man System



Cobra LifeLink Twin-Man System

MOBILE FALL PROTECTION SYSTEMS WHEN AND WHERE YOU NEED THEM

Distributed By
FRS
CANADA

465 Lucas Ave, Winnipeg, MB, R3C 2E6
Ph (204) 774-5079 Fax (204) 775-6142
email: info@frsmb.com

2601 Niagara Lane
Plymouth, MN 55447
(763) 694-2624
www.railguard.net

GARLOCK
SAFETY SYSTEMS

GARLOCK
SAFETY SYSTEMS



COBRA LIFELINK™

PATENT PENDING

Multi-Man Solution

Twin-Man Solution

Fall Arrest 3 Man & Fall Restraint 2 Man

Fall Arrest 1 Man & Fall Restraint 1 Man

The Multi-Man Cobra LifeLink Fall Protection Cart is the perfect anchorage solution for multiple workers exposed to fall from height hazards. This system is designed for up to 3 persons working at a leading edge for fall arrest and 2 persons rigged for fall restraint - all simultaneously.

The Cobra LifeLink is the latest fall protection innovation providing workers with safe, secure anchorages when doing elevated leading edge work. Whether it's construction sites, roofing jobs or doing routine maintenance on industrial plants, the Cobra LifeLink Cart is an important part of any comprehensive fall protection plan for workers.



Many job sites or flat-roofed facilities lack OSHA compliant tie-off points for workers doing leading edge work. Using sub-standard anchorages like vent pipes, or air conditioners, places workers at extreme risk — liability for the contractor or building owner is equally high.

The Cobra LifeLink system solves this problem by providing a secure OSHA compliant mobile anchorage that moves along with the worker. The Cobra Multi-Man Cart is designed for 3 workers in fall arrest and 2 workers in fall restraint. The system does not require any mechanical anchorage into the substrate, which means no penetrations, leaks or damage to sensitive surfaces.

In the event of an actual fall, the engagement claw located safely underneath the cart instantly engages itself into the substrate, holding the cart and worker secure. No fall means no engagement of claw mechanism.

The Cobra LifeLink Multi-Man Cart complies with OSHA 1926.502(d) as a fall arrest anchorage. Once engaged, the Multi-Man Cobra Cart is capable of arresting the fall of up to (3) 310 lb workers.



Many jobsites simply don't require fall protection for multiple workers. The Twin-Man Cobra LifeLink Cart is a great solution, particularly on jobsites where large expanses need to be covered or small detail work needs to be done. The modular design of the Twin-Man unit makes it easy to load in pickups, transport up elevators, and get through doorways. The Cobra Twin-Man greatly increases productivity by offering the maximum freedom of movement while still being tethered to an OSHA compliant fall arrest system.



Use the two-wheeled cart to load weights and position Cobra Cart where needed.

Sometimes a worker doing leading edge work needs help. The Cobra Twin-Man Cart comes with a fall-restraint ring to tie off an additional worker.



The Cobra LifeLink Twin-Man Cart complies with OSHA 1926.502(d) as a fall arrest anchorage. Once engaged, the Twin-Man Cobra Cart is capable of arresting the fall of (1) 310 lb. worker.



The Cobra LifeLink Twin-Man Cart is so affordable each worker can have their own! Make them responsible for inspection and care of their own cart. This makes the worker accountable and ensures that the cart is kept in top working order.



Compact design goes almost anywhere!

USE ONLY ON LOW SLOPE SURFACES OF 1/2:12 PITCH OR LESS
SUITABLE SUBSTRATES

MULTI-MAN

- Built-Up Roofing Systems
- PVC / TPO / EPDM Adhered Membranes
- Metal Decks 20ga. - 22 ga.
- Adhered Plywood - Hardboard Decking
- Adhered ISO / EPS Insulation Board
- 4000 psi Lightweight Concrete (2 man arrest)

TWIN-MAN

- Built-Up Roofing Systems
- PVC / TPO / EPDM Adhered Membranes
- Metal Decks 20ga. - 22 ga.
- Adhered Plywood - Hardboard Decking
- Adhered ISO / EPS Insulation Board
- 4000 psi Lightweight Concrete