

13 HP Ultra Cutter

The Top Choice of Roofing Pro's Everywhere

Electric Start



Honda

**NOW WITH
ELECTRIC
START**



SUPERIOR ENGINEERING DESIGN MAKES THE ULTRA CUTTER THE SMOOTHEST, MOST DEPENDABLE ROOF CUTTER ON THE MARKET TODAY!

• PROVEN DURABILITY:

Our exclusive Uni-form design creates a much stronger machine overall by replacing as many welded joints as possible with one piece of formed metal. We've built the Ultra Cutter to withstand the most rigorous field conditions by using heavy 7 gauge construction on the motor mount and 10 gauge on the the blade guard. Even the handle is supported by heavy rectangular tubing. No one else comes close to this type of strength.

• MAXIMUM CUTTING PERFORMANCE:

Our unique carbide blade design and proper weight ratio over the blade provides efficient cutting performance. The blade guard design enhances debris containment, reduces dust and improves overall safety.

Where Better Engineering Comes Out On Top

GARLOCKTM
EQUIPMENT COMPANY

2601 Niagara Lane
Plymouth, MN 55447
(800) 328-9522
(800) 820-3268 fax
www.garlockequip.com



The blade guard offers unparalleled access to the blade components. Simply lift up on one end. There are no bolts to remove. The guard pivots on the back mounting to follow the contour of the roof and it's low clearance above the roof surface contains debris from the blade.

Our clean air intake design keeps the engine cooler by drawing in clean, cool air from behind the machine and not dirt laden air near the blade.



We even included an on-board tool to change the blade and belt. To change the belt, simply remove blade cover, slide the engine forward and slip off the old belt. Our triple-wide v-belt provides 50% higher horsepower rating than conventional belts and prevents belt from rolling over.



Available in 9 or 11 hp
Honda Engine Models



Handles 12' & 14"
Carbide Blades.
Dual and Quad-tipped
Styles Available.



The threaded shaft of the depth control is protected up high near the top of the cutter instead of down low by the front wheel like some other models. The thrust bearing also helps to make finite blade depth adjustment a snap!

Specifications:

Weight.....	275 lbs
Height.....	37"
Length.....	60"
Width.....	28"



2601 Niagara Lane
Plymouth, MN 55447
(800) 328-9522
www.garlockequip.com

Distributed by:



465 Lucas Ave, Winnipeg,
MB. R3C 2E6
Ph (204) 774-5079 Fax (204) 775-6142
email: info@frsmb.com