

New Hi-Lo Carrier



- Tank height adjustable for the job. Draincock discharges from 30½" down to 22½".
- Dual swivel wheels for maneuverability.
- Foot pedal brake - step down, it's locked.
- Designed for use with Garlock's 55 gallon insulated or regular hot tanks. (Tanks sold separately. Or go for the package deal with carrier, tank and draincock).

Specifications

Length67"
Width46"
Height46"
Weight119 lbs.
Tirestwo 4.80/400x8two 10x2.75
Loaded weight w/55 REG643 lbs.
Loaded weight w/55 INS683 lbs.

For your safety, wear faceshield and long sleeved cotton shirt when filling tank - dress for the job.

* based on 8 lbs. per gallon.

Keep your "HOT" hot, in the right spot.

GARLOCK
EQUIPMENT COMPANY

2601 Niagara Lane
Plymouth, Minnesota U.S.A. 55447
(763) 553-1935

Distributed by:

FRS
CANADA
A Division of THE FRS GROUP INC.

465 Lucas Ave, Winnipeg,
MB. R3C 2E6
Ph (204) 774-5079 Fax (204) 775-6142
email: info@frsmb.com



Hoistable Lugger

The Hoistable Lugger combines the Hi-Lo Carrier and Hot Tank to provide the only safe way to hoist hot.

Three built-in lifting cables make hookup easy and a guard tube protects the draincock from damage. Available in a 55 gallon insulated model, the Hoistable Lugger weighs 236 lbs. and has two (2) 4.00 x 8 x 1" tires and two (2) 10 x 2.75 x 5/8" wheels.